

See discussions, stats, and author profiles for this publication at: <http://www.researchgate.net/publication/260979873>

Neurophysiological methods for monitoring brain activity in serious games and virtual environments: A review

ARTICLE *in* INTERNATIONAL JOURNAL OF TECHNOLOGY ENHANCED LEARNING · JANUARY 2014

DOI: 10.1504/IJTEL.2014.060022

CITATIONS

5

DOWNLOADS

99

VIEWS

234

16 AUTHORS, INCLUDING:



Milos Kravcik

RWTH Aachen University

82 PUBLICATIONS 526 CITATIONS

SEE PROFILE



T. Lim

Heriot-Watt University

84 PUBLICATIONS 283 CITATIONS

SEE PROFILE



Sandy Louchart

Heriot-Watt University

63 PUBLICATIONS 664 CITATIONS

SEE PROFILE



Riccardo Berta

Università degli Studi di Genova

86 PUBLICATIONS 337 CITATIONS

SEE PROFILE

Neurophysiological methods for monitoring brain activity in serious games and virtual environments: A review.

Authors: Manuel Ninaus, Silvia Erika Kober, Elisabeth V.C. Friedrich, Ian Dunwell, Sara de Freitas, Sylvester Arnab, Michela Ott, Milos Kravcik, Theodore Lim, Sandy Louchart, Francesco Bellotti, Anna Hannemann, Alasdair G. Thin, Riccardo Berta, Guilherme Wood, Christa Neuper

Manuel Ninaus:

M.Sc., PhD-Student

Department of Psychology, Section Neuropsychology

University of Graz

Universitätsplatz 2/III

8010 Graz

Austria

manuel.ninaus@uni-graz.at

Manuel Ninaus is Research Assistant and PhD-candidate at the Department of Psychology (Section Neuropsychology) at the University of Graz, Austria. He received his MSc in Psychology from University of Graz, Austria in 2012. Since 2010 he works as Research Assistant at the Department of Psychology and at the University of Graz and is involved in national and international scientific projects. He is currently involved in the EU GALA Network of Excellence (www.galanoe.eu). His research topics are neuronal plasticity through learning, EEG-based neurofeedback and auditory mirror neurons. Furthermore Manuel Ninaus has many years of experience with different neurophysiological methods such as EEG, NIRS and fMRI.

Silvia Erika Kober:

Dr., Postdoctoral researcher

Department of Psychology, Section Neuropsychology

University of Graz

Universitätsplatz 2/III

8010 Graz

Austria

silvia.kober@uni-graz.at

Silvia Erika Kober is a postdoctoral researcher at the Department of Psychology (Section Neuropsychology) at the University of Graz, Austria. Born in Graz, Austria, she received her MSc in Psychology from University of Graz, Austria in 2009 and obtained the Ph.D. degree from the University of Graz, Austria in 2012. Since 2007 she works as Research Assistant at the Department of Psychology (Section Neuropsychology) at the University of Graz and is involved in national and international scientific projects. Her research topics are EEG/NIRS-based brain-computer communication and neurofeedback, interacting in virtual realities, virtual reality as rehabilitation tool and spatial cognition.

Elisabeth V.C. Friedrich:

Dr., Postdoctoral researcher

Department of Psychology, Section Neuropsychology

University of Graz
Universitätsplatz 2/III
8010 Graz
Austria

elisabeth.friedrich@uni-graz.at

Elisabeth V.C. Friedrich studied Psychology at the University of Graz, Austria, and conducted her master thesis at the Laboratory of Neural Injury and Repair, Wadsworth Center, Albany, NY. She has received her doctorate in natural science in 2012 at the University of Graz, Austria. Her main research interest is brain-computer interface (BCI). She explored different mental tasks to control an EEG-based BCI, the impact of distraction on user performance as well as improvements of BCI usability for severely motor impaired individuals. She is currently involved in the EU GALA Network of Excellence (www.galanoe.eu).

Ian Dunwell:

Dr., Postdoctoral researcher
The Serious Games Institute
Coventry University Technology Park
Innovation Village
Cheetah Road
Coventry
CV1 2TL
United Kingdom

IDunwell@cad.coventry.ac.uk

Ian Dunwell is a senior researcher at the Serious Games Institute. He holds a BSc in Physics from Imperial College London and a PhD in Computer Science from the University of Hull. He has responsibility for a wide portfolio of health-related Serious Game research and development projects. He is also the Technical Lead for the Applied Research Group.

Sara de Freitas:

Prof., Director of Research at the Serious Games Institute
The Serious Games Institute
Coventry University Technology Park
Innovation Village
Cheetah Road
Coventry
CV1 2TL
United Kingdom

s.defreitas@coventry.ac.uk

Sara de Freitas is director of research at the Serious Games Institute, Professor of Virtual Environments and Fellow of the Royal Society of Arts. Sara leads the applied research team at the Serious Games Institute and the Serious Games and Virtual Worlds Applied Research Group at Coventry University.

Sylvester Arnab:

Senior researcher, PhD
The Serious Games Institute
Coventry University Technology Park
Innovation Village

Cheetah Road
Coventry
CV1 2TL
United Kingdom

s.arnab@coventry.ac.uk

Sylvester Arnab is a senior researcher at the SGI. He holds a doctorate from The University of Warwick and he is coordinating the SGI's contribution to the EU Funded Games and Learning Alliance (GALA).

Michela Ott:

Dr., Researcher
Istituto Tecnologie Didattiche (ITD)
Consiglio Nazionale delle Ricerche (CNR)
Via De Marini, 6
16149 Genova
Italy

ott@itd.cnr.it

Michela Ott is a senior researcher at the Institute for Educational Technology of Italian National Research Council. She carries out research in the fields of: cognitive processes underpinning learning, educational use of software tools (with a special focus on Serious Games), special education, e-inclusion, learning design, distance education. She is the author of more than 150 scientific publications. She is also the author of educational software packages and hypermedia systems. She has participated in, led and coordinated a number of national and international research projects in the field of Educational Technology. At present she is the coordinator of the MAGICAL (MAking Games in CollaborAtion for Learning- KA3 LLP project), is involved in the eSG LLP project (Stimulating Entrepreneurship through Serious games-Erasmus FEXI) and in three European networks: GaLA (Game and Learning Alliance); V-MuST.net (Virtual Museum Transnational Network) and ETNA (European Thematic Network on Assistive Information and Communication Technologies).

Milos Kravcik:

Dr., Research Associate
Informatik 5 – Information Systems
RWTH Aachen University
Ahornstr. 55
52056 Aachen
Germany

kravcik@dbis.rwth-aachen.de

Milos Kravcik has a diploma degree in computer science and a doctoral degree in applied informatics from the Comenius University in Slovakia. He has been dealing with Technology Enhanced Learning (TEL) since 1988 in various national and international projects, later also at the Fraunhofer Institute for Applied Information Technology in Germany and at the Open University in the Netherlands. Since 2010 he works as a Research Fellow at the RWTH Aachen University and his main research interests include personalized learning environments and self-regulated learning. He co-organized several TEL doctoral schools and serves also as executive peer-reviewer or editorial board member for several journals related to learning technologies.

Theodore Lim:

Dr., Lecturer
School of Engineering & Physical Sciences; Mechanical Engineering
NS G.04, Heriot-Watt University
Edinburgh
EH14 4AS
United Kingdom
t.lim@hw.ac.uk

Theodore Lim is an active member within the Digital Tools Group; part of the EPSRC-funded Innovative Manufacturing Research Centre (IMRC) at Heriot-Watt University (www.smi.hw.ac.uk). As both an academic and researcher with considerable industrial experience, he has been instrumental in the research, analysis and development of virtual engineering environments in a variety of product engineering domains and now focuses his work on the acquisition of engineering knowledge information management systems within all aspect of product engineering; with a particular emphasis on conceptual design. He has also implemented game-based learning methods in design and manufacturing taught courses. With over 40 international publications, a book and the successful commercialisation of his novel feature recognition algorithms, he is now applying his knowledge and expertise to the domain of serious games, game ware and computational biometrics for next generation engineering applications.

Sandy Louchart:

Dr, Lecturer
School of Mathematical & Computer Sciences; Computer Science
EM1.38, Heriot-Watt University
Edinburgh
EH14 4AS
United Kingdom
s.louchart@hw.ac.uk

Sandy Louchart is a lecturer in Human Computer Interaction and Interaction Design in the School of Mathematical and Computer Sciences (MACS) at Heriot-Watt University. His PhD, awarded by the University of Salford in 2007, explored the domain of Interactive Storytelling (IS) via the development of the Emergent Narrative concept. The work was conducted in the domains of Artificial Intelligence, Synthetic Characters and Interactive Narratives and involved the design of Autonomous Synthetic Characters and their affect-based action/selection mechanisms to simulate characterisation within an interactive drama scenario. The research led to the development of a novel approach to Synthetic Character action/selection mechanisms featuring projection-based affective planning so as to select dramatically intense actions and events for interaction; the Double Appraisal action/selection mechanism. His work has been published internationally in Intelligent Agents, Virtual Reality, Game and Interactive Storytelling Journals and Conferences.

Francesco Bellotti:

Assistant Professor, Dr.
ELIOS Lab; Department of Naval, Electrical, Electronic and Telecommunications Engineering
(DITEN)
University of Genoa
Via Opera Pia 11a
16145 Genova
Italy
franz@elios.unige.it

Francesco Bellotti is assistant professor at the Department of Naval, Electrical, Electronic and Telecommunications Engineering (DITEN) of the University of Genoa, currently teaching Object Oriented Programming and Databases. His main research interests are in the field of serious games, artificial intelligence, user modeling, neuroscientific signal analysis, technology enhanced learning and Human-Computer Interaction. He has been the responsible of the design and implementation WPs of several European and Italian industrial research projects. He is in the coordinating team of Games and Learning Alliance (GaLA), the FP7 Network of Excellence on serious games within technology enhanced learning, and of eSG, an Erasmus Lifelong Learning project aimed at promoting entrepreneurship in higher education through serious games. He is the responsible of the Infomobility Lab at the Liguria District of technologies. He authored 120+ papers in international journals and conferences.

Anna Hannemann:

Dipl. –Inform.

Informatik 5 – Information Systems

RWTH Aachen University

Ahornstr. 55

52056 Aachen

Germany

hannemann@dbis.rwth-aachen.de

Anna Hannemann is a PhD student at Information Systems of the RWTH Aachen University. She holds a Diploma in Computer Science from RWTH Aachen University. Within the EU-founded Network of Excellence for Serious Games (GALA, www.galanoe.eu), she works on serious gaming in context of neuroscience, community nurturing and interactive storytelling. Her research interests include analysis of digital social networks and design of innovative social engineering and learning techniques. She was a supervisor of the lab course ‘Gaming Communities’ at the RWTH Aachen University.

Alasdair G. Thin:

Dr., Lecturer

School of Life Sciences

Heriot-Watt University

Edinburgh

EH14 4AS

United Kingdom

a.g.thin@hw.ac.uk

Biographical notes:

Alasdair G. Thin is a Lecturer in Human Physiology in the School of Life Sciences at Heriot-Watt University, Edinburgh, UK. He has a BSc in Physiology and Sports Science, Postgraduate Certificates in Information Technology and Academic Practice and a Doctorate in Clinical Exercise Physiology. He first got interested in Serious Games at the beginning of 2004 after a chance encounter with some of the early EyeToy Play games for the Sony Playstation 2 that left him somewhat breathless! Having previously worked in health promotion, his research interests include how Serious Games can potentially act as a gateway to starting and maintaining a physically active lifestyle as well as wider health applications.

Riccardo Berta:

Assistant Professor, Dr.

ELIOS Lab; Department of Naval, Electrical, Electronic and Telecommunications Engineering (DITEN)

University of Genoa

Via Opera Pia 11a

16145 Genova

Italy

berta@elios.unige.it

Riccardo Berta is Assistant Professor at ELIOS Lab (DITEN), University of Genoa. He is teaching "Programming Fundamentals" (6 ECTS) in the Electronic and Information Technology Bachelor Course and "Multimedia Digital Entertainment" (10 ECTS) in the Electronic Engineering Master Course. His main research interests are in the field of Serious Gaming (design, implementation and evaluation), Technology Enhanced Learning (TEL) and HCI with mobile devices. He is currently involved in the EU GALA Network of Excellence (www.galanoe.eu). He authored about 90 papers in international journals and conferences.

Guilherme Wood:

Associate Professor, Dr.

Department of Psychology, Section Neuropsychology

Karl-Franzens-Universität Graz

Universitätsplatz 2/III

8010 Graz

Austria

guilherme.wood@uni-graz.at

Guilherme Wood is Assistant Professor at the Department of Psychology at the University of Graz in Austria. Guilherme Wood received his master degree in Psychology from the Federal University of Minas Gerais (Brazil) and his PhD at the RWTH University Aachen, Germany. His research foci are neurofeedback, the impact of aging on cognition and brain function, neurocognitive aspects of number processing and the genetic correlates of cognitive and brain activity.

Christa Neuper:

Prof., Rector of the University of Graz

Department of Psychology, Section Neuropsychology

University of Graz

Universitätsplatz 2/III

8010 Graz

Austria

christa.neuper@uni-graz.at

Christa Neuper obtained the Ph.D. degree from the University of Graz (UniGraz), Austria in 1984. During 1985-1986 she worked as Scientific Co-worker at the Department of Psychology at UniGraz. Between 1990 and 1994 she was University Assistant at the Institute for Biomedical Engineering, Department of Medical Informatics, University of Technology Graz (TUGraz), Austria, and during 1994-2005 she worked as Senior Scientist at the Ludwig Boltzmann-Institute for Medical Informatics and Neuroinformatics, TUGraz. She was Assistant Professor at the Department of Psychology, UniGraz, where she has the rank of a full professor of 'Applied Neuropsychology: Human-Computer Interface' since 2005. Additionally, since 2010 she has the rank of professor at the Institute for Knowledge Discovery, Laboratory of Brain-Computer Interfaces at TUGraz. Since 2011 she is rector of the University of Graz. Her research topics are EEG-based brain-computer communication and

neurofeedback, event-related brain oscillations and cognition, and sensorimotor processing in motor actions and motor imagery.

Acknowledgements:

This work was supported by the Games and Learning Alliance (GaLA) - Network of Excellence for Serious Games under the European Community Seventh Framework Programme (FP7/2007 2013), Grant Agreement no. 258169.

Abstract

The use of serious games and virtual environments for learning is increasing worldwide. These technologies have the potential to collect live data from users through game-play and can be combined with neuroscientific methods such as EEG, fNIRS and fMRI. The several learning processes triggered by serious games are associated with specific patterns of activation that distributed in time and space over different neural networks. This paper explores the opportunities offered and challenges posed by neuroscientific methods when capturing user feedback and using the data to create greater user adaptivity in-game. Existing neuroscientific studies examining cortical correlates of game-based learning do not form a common or homogenous field. In contrast, they often have disparate research questions and are represented through a broad range of study designs and game genres. In this article, the range of studies and applications of neuroscientific methods in game-based learning are reviewed.

Keywords:

neurophysiological methods; brain; serious games; games; virtual environments; virtual reality; NIRS; near infrared spectroscopy; EEG; electroencephalography; fMRI; functional magnetic resonance imaging; neuroscience; learning; game based learning.

1. Introduction and background

Serious games are increasingly adopted as novel solutions for supporting educational and training activities (e.g. de Freitas and Maharg, 2011; Zyda, 2005). There are at least two ways in which neuroscientific methods of collection of brain activity can be used to provide information for serious games and virtual environments. Firstly, these methods are useful to assess the efficacy of game-based approaches. As with any other learning technology, the efficacy and value of game-based approaches must be carefully assessed, particularly in terms of their wider role in blended or exploratory pedagogic approaches (e.g. de Freitas and Neumann, 2009). Secondly, these methods are suitable to enhance game adaptivity to the user by collecting user data dynamically. Neuroscientific methods can be used to collect brain activity and then be used as feedback to the user, allowing the game to adapt to the user's interactions and inputs.

This paper considers both of these approaches in relation to a literature review and an assessment of some key studies in the field. This review examines neuroscientific studies on computer games, serious games and virtual environments with regard to learning processes, such as attention, cognitive workload, sense of presence and immersion. An extensive examination of the scientific literature was undertaken. This approach was not restricted to any specific time frame but included all the literature available in databases such as PubMed, ScienceDirect and Scopus. Additionally, other relevant conference proceedings and the expertise of the authors were utilised.

Regarding the assessment of the efficacy of game-based approaches, action video games have been shown to enhance a wide variety of perceptual skills such as visual selective attention (Green and Bavelier, 2003) and spatial attention and mental rotation (Feng, Spence and Pratt, 2007). However, some studies report that extensive video game practice does not significantly enhance performance in several cognitive abilities, such as attention, memory and executive control in non-gamers (Boot et al., 2008). Yet, extensive experience with action video games may enhance players' top-down attentional control, which can help them to rapidly distinguish between relevant and irrelevant information (Chisholm et al., 2010). Some researchers assume that video game experience can improve the ability to extract task-relevant information, especially in the domain of visual perception (Green, Li and Bavelier, 2010). However, there are many more aspects to consider such as expectations (Bengtsson et al., 2009), the sense of agency (Sharot, Velasquez and Dolan, 2010), personal experience (Sharot et al., 2007), flow (e.g. Berta et al., 2013) and the brain reward system (Clark, 2010). For effective transfer of learning to occur, users need sufficient practice with the serious game and therefore the game has to be sufficiently compelling for users to put in the requisite amount of time and effort (Suilleabhain, 2008).

Regarding the enhancement of game adaptivity, a diverse range of human computer interaction (HCI) technologies and methods have been employed in serious games. Several studies examined how these novel interfaces, such as haptics and augmented reality, can be effectively integrated with game-based learning (Arnab et al., 2010; Bellotti, Berta and De Gloria, 2010; Liarokapis et al., 2009; Prensky, 2003). Amongst these HCI studies with games, neuroscientific methods provide a new and relevant approach allowing for identifying the quality of affective feedback from users (e.g. Rebolledo-Mendez et al., 2009). Given the close relationship between cognitive learning processes and neurophysiology this is perhaps unsurprising. However, the issue of how user inputs can be fed back into the game adaptivity is an emerging line of game-related research not only to provide efficacy but also as an adaptive element in HCI and games. Recently, specific brain regions have been identified that indicate brains' preparedness to learn (Yoo et al., 2012). This shows new challenges for learning improvement if a link between brain activity and learning success can be solidly proven in dynamic learning games

studies. One area of use of the research in applied learning situations consists in training how to make the player enter the ‘prepared’ brain states before learning starts. Another field of investigation is stimulating areas of the brain that are to be involved in the learning process. It has been shown that externally modulating the brain activity can boost its performance in arithmetic (Cohen-Kadosh et al., 2010), problem-solving (Chi and Snyder, 2012), language learning (Flöel et al., 2008) and movement (Reis et al., 2009). Additionally, real-time strategy video games can train executive control functions, such as task switching, working memory, visual short-term memory and reasoning (Basak et al., 2008).

The neuroscientific method most often used in a gaming environment is electroencephalography (EEG). EEG is commonly favoured for its lightweight, non-invasive and unobtrusive nature. However, other neurophysiological methods such as functional magnetic resonance imaging (fMRI) and functional near-infrared spectroscopy (fNIRS) are also increasingly popular as a technique to assess and understand learning processes in game environments. In the next section, we outline a range of examples of the use of these techniques, and discuss the various indicators they can provide to the learning process, as well as how this information can be fed back to learners, inform educators or function as a control input for reinforcing feedback.

2. Applications of neuroscientific methods in game-based learning

In this section, applications of neuroscientific methods in game-based learning environments are broadly classified in terms of the underlying technology: EEG, fMRI and fNIRS. For each technology, a range of studies is presented, which has shown relevance for measuring physiological states or transitions, and factors salient to learning processes, such as attention, cognitive workload, sense of presence and immersion (Table 1). Additionally, we will highlight the strengths and weaknesses of these neuroscientific methods. Following this description, the discussion section critically identifies the commonalities in these studies and suggests a number of research areas that we consider as key to be addressed in the future.

Table 1: Neuroscientific studies for monitoring brain activity in serious games and virtual environments

Reference	Neuroscientific Method	Method	Purpose
Allison and Polich, 2008	EEG	Game	Using ERPs to assess cognitive workload during gaming
Pugnetti et al., 1996	EEG	Virtual Reality	Navigating through an interactive virtual environment; Using ERPs to get insight about participants’ engagement level
Kober and Neuper, 2012	EEG	Virtual Reality	Navigating through an interactive virtual environment; Using ERPs to get insight

			about participants' engagement level
Salminen and Ravaja, 2007	EEG	Game	Gaming events with different cognitive demands were associated with EEG oscillations changes
Kramer, 2007	EEG	Game	EEG oscillations used as predictors of performance in video game
Yamada, 1998	EEG	Game	EEG oscillations to assess attention, concentration, fatigue and interest during gaming
Nacke, Grimshaw and Lindley, 2010	EEG	Games	Modulations in EEG during gaming related to mental effort
Pellouchoud et al., 1999	EEG	Games	Modulations in EEG during gaming related to mental effort
Salminen and Ravaja, 2008	EEG	Games	Modulations in EEG during gaming related to mental effort
Baumgartner et al., 2006	EEG	Virtual Reality	Assessing the presence experience in games with EEG
Kober, Kurzmann and Neuper, 2012	EEG	Virtual Reality	Assessing the presence experience in games with EEG
Plotnikov et al., 2012	EEG	Game	Measuring flow with EEG
Berta et al., 2013	EEG	Game	Measuring flow with EEG
Kosmadoudi et al., 2010	EEG	Game-based environment	Stress levels recorded with EEG and galvanic feedback in a game-based environment
Liu et al., 2010	EEG	Virtual Reality	Using EEG and Galvanic Skin Response to assess emotional status of the user
Finke, Lenhardt and Ritter, 2009	EEG	Game	EEG BCI used for controlling a character on a three-dimensional game board
Nijholt, Plass-Oude Bos and Reuderink, 2009	EEG	Review	BCI
Scherer et al., 2013	EEG	Game	Controlling a MMORPG with a BCI
Lin and John, 2006	EEG	Game	Quantifying Mental Relaxation with EEG

			in a simple computer game
Ninaus et al., 2013	EEG	Review	Neurofeedback
Rebolledo-Mendez et al., 2009	EEG	Virtual Reality	EEG to assess attention levels
Hummer et al., 2010	fMRI	Game	Examining the impact of a violent video game on the brain
Mathiak and Weber, 2006	fMRI	Game	Examining the impact of a violent video game on the brain
Wang et al., 2009	fMRI	Game	Examining the impact of a violent video game on the brain
Baumgartner et al., 2008	fMRI	Virtual Reality	Cortical correlates of presence experience
Jäncke, Cheetham and Baumgartner, 2009	fMRI	Virtual Reality	Cortical correlates of presence experience
Klasen et al., 2012	fMRI	Game	Cortical correlates of flow
Goebel et al., 2004	fMRI	Game	Controlling a computer game based on table tennis
Izzetoglu et al., 2004	fNIRS	Game	Game difficulty associated with oxygenation levels
Matsuda and Hiraki, 2006	fNIRS	Game	Examining cognitive load of video games
Nagamitsu et al., 2006	fNIRS	Game	Examining the attention demand or task load from video games
Hattahara et al., 2008	fNIRS	Game	Identifying differences in changes in blood oxygenation between novice players and master-level players
Girouard et al., 2009	fNIRS	Game	Blood oxygenation differences were used to distinguish between low and high game difficulty
Tachibana, et al., 2011	fNIRS	Game	Insights into temporal relationships of blood oxygenation during real motor tasks by using a dance video game
Matsuyama, Asama, & Otake, 2009	fNIRS	Game	Controlling a humanoid robot with real-time fNIRS

2.1. EEG

With EEG, electrical activity of the brain can be recorded non-invasively at the scalp surface, which reflects the summed potential of ionic currents across membranes of single cells, thus a direct method of measuring brain activity. Electrodes placed on the scalp pick up the signals mostly from brain regions near the surface of the head (Kropotov, 2009). These signals can be differentiated in two groups: First, the Event-Related Potentials (ERPs), such as P300 evoked potentials. The occurrence of particular events or stimuli can induce changes in the activity of neuronal populations that are generally called ERPs. Generally, averaging procedures are used to identify such ERPs (Pfurtscheller and Lopes da Silva, 1999). Second, the event-related changes in the ongoing EEG activity in specific frequency bands, such as desynchronization or synchronization of alpha and beta rhythms. Due to the fact that EEG is based on measuring electrical brain activity, it has a very high temporal resolution and can detect changes of brain activation within milliseconds.

EEG applications in game-based learning: In many EEG studies neuronal responses to instantaneous game events are recorded. By averaging these events, ERPs can be detected (Pfurtscheller and Lopes da Silva, 1999). For instance, ERPs can then be used to assess cognitive workload during gaming. In so called dual-task paradigms, infrequent game-unrelated stimuli such as tones are presented during playing games. These stimuli can elicit ERPs in the EEG. There is evidence that the amplitude of these ERP varies depending on the cognitive workload induced by playing a game (Allison and Polich, 2008).

General effects of interaction with virtual environments on nervous system activity have already been explored in the 1990s. Pugnetti and colleagues (1996) investigated the correlates of virtual reality experience using EEG. They implemented interactive virtual environments with tasks similar to those of well-established tests of categorisation and cognitive flexibility, e.g. the Wisconsin Card Sorting Test (WCST). For instance, participants had to navigate quickly from one virtual room to the next until the virtual environment exit was reached. Additionally, during the navigation task cortical auditory ERPs were elicited by releasing footstep sounds binaurally as they moved forward in the virtual world. Engaging in the virtual reality task substantially reduced the amplitude of specific ERP components. This result might show that if participants are engaged in virtual environments, only a fraction of their processing abilities is devoted to stimuli such as the footstep sounds, which they did not have to process actively. Hence, the amplitudes of auditory ERP in the EEG elicited by footsteps sounds were reduced.

In a recent study by Kober and Neuper (2012), auditory ERPs elicited through presentation of infrequent tones were used to examine attention allocation between virtual reality (VR) and the real world. ERP amplitudes could differentiate between participants that focused their attention on VR (highly engaged) and participants that were less immersed in VR (less engaged). This study may demonstrate a new and objective way of measuring engagement respectively the sense of presence in a virtual environment. Highly engaging virtual environments may support attention and therefore learning. The question on what specific learning content a highly engaging virtual environment is beneficial has not been answered yet.

Besides analysing time-locked ERPs, the EEG can be recorded continuously during a gaming session. The continuous EEG oscillations during gaming may then be compared with the EEG activity during a resting or baseline period before or after playing a game. These EEG oscillations can shed light on

cognitive and emotional processes underlying the gaming process (Niedermeyer and Lopes da Silva, 2005). For example, oscillatory brain responses evoked by video game events were examined by Salminen and Ravaja (2007). They found that gaming events with different cognitive demands were associated with different changes in EEG oscillations. There is also evidence that EEG oscillations can be used as predictors of performance in video games (Kramer, 2007). Furthermore, EEG oscillations are useful for assessing attention, concentration, fatigue, and interest during playing games (Yamada, 1998). Generally, changes in EEG oscillations during gaming were examined in the context of different research questions, such as oscillatory activation induced by violent video games, mental effort related EEG modulation during gaming and affective game-play interaction (Nacke, Grimshaw and Lindley, 2010; Pellouchoud et al., 1999; Salminen and Ravaja, 2008).

Using EEG recordings, Baumgartner and colleagues (2006) found a positive relationship between presence experiences (sense of being there, Slater, 2003) in virtual worlds and cortical activation in parietal brain areas known to be involved in spatial navigation. The subjects' task was to passively watch different immersive virtual roller coaster scenarios during the EEG measurement and to rate their feeling of presence. Users experiencing a higher level of presence showed an increased event-related desynchronization (ERD) in the Alpha band (8-13 Hz) reflecting increased activation (Pfurtscheller, 1989) in parietal brain regions. Kober, Kurzman and Neuper (2012) could replicate these findings in an interactive virtual environment, where subjects navigated freely through a virtual world. Baumgartner and colleagues (2006) and Kober, Kurzman and Neuper (2012) concluded that parietal brain areas might play an important role in the presence experience because these areas are involved in generating an egocentric (body-centred) representation of space (Maguire et al., 1998; Maguire, Burgess and O'Keefe, 1999). Because the presence experience is among other definitions also defined as egocentric spatial experience of virtual worlds, it might be that an egocentric view provided by the parietal lobe is essential for the spatial presence experience in virtual environments (Baumgartner et al., 2008; Jäncke, Cheetham and Baumgartner, 2009; Kober, Kurzman and Neuper, 2012).

A further interesting empirical study, where neurophysiological methods have been used to examine game related subjective experiences, was conducted by Plotnikov and colleagues (2012; see also Berta et al., 2013). The researchers reported initial data on the monitoring of the player flow status with a commercial 4 electrode EEG. The study examined if it is possible to statistically distinguish a flow from a boredom condition. The results - even if limited because of the small sample size of the test - are promising and enable further research.

EEG has also been used to investigate the stress level in order to find out how the design of the user interface could affect an engineers' productivity (Kosmadoudi et al., 2010). The research questioned whether a game-based environment for engineering product design could bring about any positive benefits. The pilot study indicated that as design tasks transit from precise engineered shapes to freeform, performance and stress levels recorded with EEG frequencies and galvanic feedback in a game-based design environment were significantly lower. The exercise was meant to distinguish the difference in cognitive load and interface appreciation between that of a highly structured virtual design environment and that of a lesser constraint one. The basis was on tasks rather than distinct events.

Besides using EEG for assessing and monitoring cognitive processes, EEG can also be used to provide feedback and hence make games adaptive. Continuous EEG recording with or without the combination of autonomic variables (heart rate, respiration rate) can also be used to control adaptive environments. A time-power analysis on continuous EEG and Galvanic Skin Response (GSR)

reported the emotional status of the user on an engineering design task in a computer-aided design environment (Liu et al., 2010). It revealed a non-obstructed means of evaluating the affective effects of the user interface design in a virtual environment, as well as providing the environment with the ability of adaptive automation with the human factor.

Another application field is brain-computer interface (BCI). BCIs can provide people with a new non-muscular channel for controlling games (Finke, Lenhardt and Ritter, 2009; Nijholt, Plass-Oude Bos and Reuderink, 2009; Scherer et al., 2013). BCI can be used as an extra modality added to game designs, so that gamers can consciously try to interact within the game environment. Another practical implementation of BCI in serious games could be passive BCIs (Venthur et al., 2010; Zander and Kothe, 2011) as well as neurofeedback (Lin and John, 2006; Strehl et al., 2006; for a review, see Ninaus et al., 2013). In neurofeedback applications users can learn to control their own global brain activity to get into a state of mind more suitable for learning and so optimizing learning success. In a study by Rebolledo-Mendez and colleagues (2009), a commercial BCI was tested for usability in a virtual environment using computer science learning tasks. Results showed a correlation between self-reported and actual attention levels measured by the device. Further studies are needed to examine the benefits and reliability of commercial BCIs measuring attention levels in serious games and virtual environments (Rebolledo-Mendez et al., forthcoming).

These feedback and BCI devices can be used with serious games as a source of feedback from the learner and as an interface device within the game environment, but more studies need to be undertaken to ensure that the feedback is accurate and supports positive learning transfer.

Currently there is a shift from traditional individual learning to collaborative learning environments. Collaboration presents 'coordinated effort to solve a problem together' (Roschelle and Teasley, 1995). People often have different skills and experiences. By collaborative problem solving they learn in the first place to integrate and coordinate their collective knowledge. Dumas and colleagues (2010) conducted a study, in which two persons in separate rooms were instructed to make meaningless gestures with their hands. Participants were filmed and they could see their partners' hands through the TV screen. The experiments showed that the states of interactional synchrony (similar gestures) correlated with emergence of an interbrain synchronizing network. This is in line with the notion of 'awareness' (Dourish and Bellotti, 1992) that promotes 'an understanding of the activities of others, which provides a context for your own activity' (Dumas and colleagues, 2010; Dourish and Bellotti, 1992; Halimi, Seridi and Faron-Zucker, 2011). Studies exploring the mirror neuron system - which is engaged while imitating or simulating the actions of others and might be the basis for social processes, such as imitation, empathy, action understanding and perspective taking (Rizzolatti and Craighero, 2004) - have shown different EEG activation in conditions in which participants performed synchronized finger movements together with their partner or performed finger movements on their own independently (Naem et al., 2012). Furthermore, activation of the mirror neuron system could be an indicator if a game character or robot is still 'human' enough to engage the mirror neuron system (Obermann et al., 2007).

2.2. fMRI

fMRI is a popular non-invasive neuroscientific method. Magnetic resonance imaging uses strong magnetic fields to create images of biological tissue. fMRI allows to measure participant's blood oxygenation level dependent (BOLD) response with an excellent degree of spatial resolution to give information on task-specific activation in a variety of brain regions (Detre and Wang, 2002). The BOLD reflects relative changes in the concentration of deoxygenated haemoglobin evoked by sensory, motor and cognitive processes. The concentration of deoxygenated haemoglobin increases

rapidly and peaking at about six seconds after stimulus onset, before declining to a minimum value about twelve seconds after onset and returning to baseline about ten seconds after stimulus onset (Huettel, Song, & McCarthy, 2009). Therefore fMRI can provide, among other things, relevant information about the neuroanatomical localization of regions responsible for learning and interacting in serious games and virtual environments. The information gained from fMRI can be used, for example, to improve the effectiveness of serious games or how games affect the player's brain.

fMRI applications in game-based learning: For instance, fMRI has been used to investigate how playing a violent video game impacts the player's brain. Violent scenes in the video games revealed significant modulations of BOLD response in frontal brain regions when comparing participants who played violent video games and those who did not (Hummer et al., 2010; Mathiak and Weber, 2006; Wang et al., 2009). Video games of different genre that require diverse cognitive resources lead to differences in the BOLD response (Saito, Mukawa and Saito, 2007). Hence, fMRI turned out to be a valuable tool for examining cortical correlates of the gaming process as well. An fMRI study using virtual roller coaster scenarios found that the presence experience in simulating environments is linked to activation of a distributed network in the brain, e.g. activation in the dorsal and ventral visual stream, the parietal cortex, the premotor cortex, mesial temporal areas, the brainstem, the thalamus and the dorsolateral prefrontal cortex (DLPFC) (Baumgartner et al., 2008; Jäncke, Cheetham and Baumgartner, 2009). Jäncke and colleagues (2009) supposed that the DLPFC could be a key node of this network because it modulates or down-regulates the activation of the network and consequently regulates the associated experience of presence.

Another very important construct for investigating serious games and virtual environments is "flow". Klasen and colleagues (2012) showed that even such a subjective feeling is to some extent measureable with neurophysiological methods. These authors acquired fMRI data during free play of a video game and analysed brain activity based on the game content. They developed a content coding system which allowed for a reliable and objective description of in-game events and the actions of the player. The detailed content analysis of the players' game sessions allowed the authors to analyse the fMRI data with respect to specific factors of the subjective game experience "flow". Klasen and colleagues (2012) found that flow is characterized by specific neural activation patterns in reward-related midbrain structures, as well as cognitive and sensorimotor networks. Klasen and colleagues (2012) argued that the activation in sensory and motor networks could underpin the central role of simulation for flow experience. They assume that this sensorimotor activation reflects the simulation of physical activity in the game.

Numerous cognitive properties cannot be described through single brain areas, as shown by Klasen and colleagues (2012) for "flow". The majority of cognitive processes rely on a wide-spread network in the brain. For instance, creative thinking is considered as a complex mental ability domain (Fink, Graif and Neubauer, 2009) and one of the most extraordinary capacities in humans (Dietrich and Kanso, 2010). Therefore, the exploration of neurophysiological correlates of creativity could contribute to better tune and focus specific educational actions oriented to creativity enhancement in the context of serious games. Following the examination of 72 studies including fMRI as well as EEG, Dietrich and Kanso (2010, p.822) came to the conclusion that 'creative thinking does not appear to critically depend on any single mental process or brain region, and it is not especially associated with right brains, defocused attention, low arousal, or alpha synchronization'. Haier and Jung (2008, p.171) observed that integrating neuroscience findings into education practices is 'a daunting challenge that will require educators to re-examine old ideas and acquire fundamental backgrounds in new areas'. This implies, for instance, extending and empowering group work and collaborative learning activities, taking into account that neuroscience findings have already proven that accessing

the ideas of others may enhance creativity by reducing the need to deactivate automatic bottom-up processes, associated with fixation on own ideas (Fink et al., 2010).

The different aspects of collaboration and social interaction, such as joint attention or decision-making, also have been investigated in several psychophysiological studies using fMRI, too. Williams and colleagues (2005) identified a number of clusters of additional activity in the joint attention settings in comparison to non-joint attention conditions. Furthermore, Martena, Dicke and Thier (2008) also discovered additional activation patterns in the posterior superior temporal sulcus (pSTS) region in case of joint attention. In both studies, participants had to move their eyes. In joint condition, participants should shift their gaze toward the target guided by a gaze of a face, which was presented on the screen in front of them.

Not only learning with more people but also with more modalities might have an advantage. Shams and Seitz (2008) advocated multisensory teaching approaches as mirroring more closely evolved learning processes, suggesting unisensory approaches are sub-optimal and that their selection is based in practicality rather than pedagogy. For instance, visual and auditory information are integrated in performing many tasks that involve localizing and tracking moving objects. Based on their reviews, they assume that the human brain has evolved to learn and operate optimally in multisensory environments (but see also the study of Kalyuga, Chandler and Sweller, 2004, which showed that redundant information presented in different modalities can actually interfere with learning). Recently, multisensory modulations and activations have been discovered in early stage perceptual processing brain areas, which have long been claimed as 'sensory specific' (Shams and Seitz, 2008). Shams and Seitz (2009) suggest that training protocols that employ unisensory stimulus environments do not engage multisensory learning mechanisms and, therefore, might be sub-optimal for learning. Thus, multisensory stimulus environments are more effective for learning, because they can better resemble natural settings. This finding seems to correlate with other studies in serious games research where immediate feedback to learners and multisensory environments are more effective than traditional learning approaches (Knight et al., 2010). The main lesson for serious game design here is that feedback to the learner needs to be formative in games and that multisensory environment can be more effective as a design strategy for effective learning with games.

Another application field where fMRI can provide feedback is real-time fMRI (Weiskopf, 2012). However, due to the fact that real-time fMRI is a relatively new feedback method, only a few real-time fMRI studies implemented gaming elements as feedback modality so far. For instance, self-regulated brain activity has been used to play a computer game based on table tennis inside the MRI-scanner (Goebel, Sorger, Kaiser, Birbaumer, & Weiskopf, 2004).

2.3. fNIRS

fNIRS is a non-invasive optical neuroimaging technique discovered in 1992. fNIRS can be used to explore the functional activation of the human cerebral cortex. This neurophysiological method uses the oxygenation and haemodynamic changes in the blood of the human brain (Ferrari and Quaresima, 2012). fNIRS is based on the same metabolic signal as the fMRI, the BOLD response. More precisely, fNIRS takes advantage of the different absorption spectra for near infrared light of oxygenated haemoglobin and deoxygenated haemoglobin and allows to measure relative changes in haemoglobin concentration (Villringer & Chance, 1997). fNIRS relies on the principle of neurovascular coupling, that is local neural activity leads to a vascular response in the active brain area that causes an inflow of oxygenated blood. As a result, deoxygenated haemoglobin decreases, whereas oxygenated

haemoglobin increases in the active brain region. This circumstance is the major source of the BOLD contrast as measured with fMRI (Huettel, Song, & McCarthy, 2009; Telkemeyer et al., 2011). However, fNIRS allows for the recording of changes in the BOLD response with a much higher temporal resolution than fMRI but at the costs of lower spatial resolution and no sensitivity to haemodynamic activity in deep brain regions.

fNIRS applications in game-based learning: Many game studies used fNIRS to examine haemodynamic changes in frontal brain areas during playing video games. The majority found a decrease in oxygenated-haemoglobin during gaming which might result from attention demand or task load from the video games (Izzetoglu et al., 2004; Matsuda and Hiraki, 2006; Nagamitsu et al., 2006). Additionally, fNIRS measurements were used to examine differences in blood oxygenation between novice players and master-level players (Hattahara et al., 2008). These identifiable measures between experienced and novice players have particular appeal, as they allow for the development of baselines against which future learners can be assessed.

fNIRS is also used to investigate cognitive load. Prefrontal cortex plays an important role in many higher cognitive functions and video game play leads to a reduction in oxygenated-haemoglobin which rapidly recovers after the end of a game (Matsuda and Hiraki, 2006). Girouard and colleagues (2009) used fNIRS to measure the response to both low and high game difficulty and found a significant difference between the pooled group means. However, the small effect size meant that a classifier algorithm had difficulty distinguish changes within individuals. A military simulator (Warship commander) was used to vary task difficulty while fNIRS was used to measure changes in dorsolateral prefrontal cortex oxygenation levels (Izzetoglu et al., 2004). An inverted U-type relationship where oxygenation levels increased with increasing task difficulty until it became too difficult and then they started to decline was observed. Some of the authors of this article have undertaken small pilot studies to determine whether fNIRS can be used as a valid measure of effective learning, and these studies are on-going, using simple and more complex serious games.

Besides using fNIRS for monitoring cognitive processes, fNIRS can also be used to provide real-time feedback. However, game elements have hardly been implemented in real-time fNIRS studies so far. In one of these studies, real-time fNIRS was used to control a humanoid robot. Participants performed different mental tasks to generate motion in the robot (Matsuyama, Asama, & Otake, 2009). It is conceivable that real-time fNIRS could also be used to control games or in-game characters.

2.4. Pros and cons of different neurophysiological methods

Different neurophysiological methods can be used for monitoring and assessing cognitive processes in serious games and virtual environments. However, the different methods are associated with various advantages and disadvantages. Depending on the research question, study design, and hypotheses one neurophysiological method is more suitable than the other. For instance, EEG has a high temporal resolution (< 1 msec) compared to fNIRS and fMRI (> 1 sec). Thus, using EEG to add a further possibility to interact with the game or to control the game itself, respectively, is recommendable since the electrical activity of the brain can be detected immediately and fed back to the user with no

time delay. fNIRS and fMRI, which are based on relatively slow metabolic changes, would result in a delayed feedback and the interaction with the game would not feel responsive to the user.

However, if someone is interested in examining cognitive processes and its neural substrates during gaming, especially in deep brain structures such as the amygdala or hippocampus, fMRI is a superior method. fMRI has a high spatial resolution, compared to EEG and fNIRS, and enables the researcher to make assumptions about the involvement of different brain areas and its relevance for gaming. EEG allows only limited access to deep brain structures, depending on the number of electrodes used. fNIRS enables us to measure changes in haemodynamic responses only at the surface of the brain. (Huppert, Hoge, Diamond, Franceschini, & Boas, 2006).

In neuroscientific studies the quality of the assessed neurophysiological data is crucial. Compared to EEG and fMRI, fNIRS has the advantage of a reduced sensitivity to motion-artefacts and therefore allows a higher degree of movement (Lloyd-Fox, Blasi, & Elwell, 2010; Nambu et al., 2009). Tachibana and colleagues (2011) demonstrated that fNIRS can be adequately used to measure brain activation when playing a dance video game, where participants had to move extensively. While lying inside the MRI-scanner, participants should not move their head to avoid motion artefacts which can affect the quality of the fMRI data enormously.

A further important issue is the comfort for participants during measurements, especially when examining subjective experiences during gaming such as flow. Distractions due to the neurophysiological measurements could decrease or hamper such game experiences. For instance, some participants experience discomfort inside a MRI-scanner because of the noise and the narrow scanner. The montage of EEG electrodes is with some EEG systems very time-consuming and repeated measures might be uncomfortable since there is abrasive gel needed, which could lead to skin irritations. In contrast, the preparation time for fNIRS is quite fast. Compared to fMRI, which is locally bounded to the installation site, fNIRS and EEG are more flexible and portable systems. Recently, easy-to-use and wireless devices are available which might be useful when using fNIRS or EEG in the gaming context (Muehleemann, Haensse, & Wolf, 2008; Ninaus et al., 2013; Sitaram, Caria, & Birbaumer, 2009).

Finally, it should be noted that the costs of the different neurophysiological methods are quite different. While fMRI is the most expensive method in terms of maintenance and purchase, EEG is highly cost-effective.

In summary, for the assessment of the efficacy of game-based approaches, all three discussed neuroscientific methods are more or less suitable. If examining brain responses to fast events of a game, the EEG with its high temporal resolution should be the method of choice. In contrast, for the investigation of neuronal responses during gaming in deep brain structures, fMRI with its high spatial resolution is the best choice. But if the comfort for the gamer should be maximal, fNIRS is recommended. In the context of using neuroscientific methods to enhance game adaptivity to the user, again the high temporal resolution of EEG is the most advantageous, since there is no time delay when the electrical activity of the brain is fed back to the gamer in real time during interacting with a game.

3. Discussion

One of the issues emerging from our review and on-going pilot studies is that there is a lack of a common methodological approach in the use and validity assessment of neuroscientific methods in

serious games or games in general. A primary consequence of this is a large number of studies reaching conclusions that might easily be misinterpreted. For example, Derbali and Frasson (2010) deployed a serious game which educated about the problem of world hunger. Whilst playing, the relationship between players' motivation and EEG oscillations was examined. During gaming the players' motivation, measured via survey, was shown to correlate with changes in EEG measurements. Therefore, EEG is suggested to be a valid and objective index of players' motivation during gaming. Yet this makes a significant assumption in suggesting surveyed metrics of motivation are a true proxy for the latent psychological construct – in fact how motivation is constructed, defined and influences behaviour is far from being universally defined or agreed, which can be solved only with more specific measures of stress and motivation according to established theories and the replication of studies.

This applies equally to commercially available lightweight EEG devices, which often suggest such metrics (e.g. 'attention' and 'motivation'), without providing clarity in their derivation and definition. Furthermore, the placement of the electrodes of such devices is often in a way that records muscle rather than brain activity. This is not to dispute that EEG readings can be correlated to a wide range of learning activities; rather, we argue that attempting to explain the EEG values in terms of emotions and psychological constructs is a step that can rapidly complicate the interpretation, applicability and reusability of findings. Furthermore it is important to decide what neurophysiological method will suit best to the planned research question and experimental design. For example, using fMRI can provide detailed spatial information about specific brain areas and their function, but the temporal resolution is poor, compared to EEG. However, for all neurophysiological measurements, artefacts are a problem, for some more (fMRI, EEG) for some less (NIRS). Nevertheless, the movement always has to be restricted and measurements are usually in the lab in artificial environments. This is a disadvantage for games and virtual realities in which most engagement of the user is desirable and has to be considered very carefully in study design.

Many decisions need to be taken before conducting neurophysiological measurements, therefore it is essential to have a clear experimental design and hypotheses for psychophysiological studies. For examining basic neurophysiological correlates, the used games should not be too complex. Especially for explorative studies, a simple game design with only few variables should be used to be able to clearly identify which brain processes are involved or which skills are needed during gaming. Using psychophysiological methods in game research has some apparent limitations, as discussed in the previous sections. Nevertheless, if it is used appropriately it is a powerful tool to answer various research questions related to game experience and specific states in the context of learning.

We thus argue that effective study design for serious games should avoid such dilemmas by focussing specifically on direct task performance as a correlate of device measurements. Effectively, this aims at preventing the requisite of a deeper understanding of the neurophysiological processes and psychological constructs affecting performance, while focuses on direct correlates between narrow metrics of task performance and measured readings. Serious games can form a particularly effective basis for this, as game design lends itself easily to the definition and assessment of simple cognitive tasks, as well as their deployment in an experimental context, with a wide range of user performance data collection. Study designs under such a paradigm should focus on defining and understanding expertise at a task established through an understanding of the prior knowledge or measured performance of subjects. These metrics can then be more readily correlated to measurements from EEG, fNIRS, fMRI or other biosensor devices whilst avoiding the pitfalls of attempting to reach broad conclusions regarding the nature and physiology of learning.

Another approach to obtain an effective experimental design is to apply the logic of the additive factor method by Sternberg (Sternberg, 1969). The additive factor method was originally used for reaction

time measurements to study different stages of information processing. Some of the theoretical assumptions of this method are also used in neurophysiological research. Neuroscientific experiments try to examine specific cognitive properties. By theory-based analysing the subjects' task with psychometric methods, it is possible to identify what cognitive processes or factors are involved in one specific task. Determining every cognitive process in one task is not trivial and is even harder for game environments, due to the complexity of some environments. However, with the knowledge of every cognitive process in one task it is much easier to find or design another task that includes all these processes except the one cognitive process you're interested in. By comparing these two tasks you are able to extract this specific cognitive process from your neurophysiological data.

With respect to study design, comparison of subject matter expert to novice provides a demonstrated means to establish baselines which avoid the difficulty of analysing the complexity of the underlying learning process. Generalizability of such baselines suffers from a close relationship between task and game design, and measured outputs. However, the overlying methodology, which applies baselines developed through a control study of experts against novices, can offer an immediate model for assessment of learners irrespective of task or device. This has the proviso that clear differences can be observed, and the studies we have presented suggest some outcomes which may inform this: for EEG, a common assertion is that measurements can be related to attention and focus. fMRI and fNIRS, by comparison, may offer more specific insight into performance in narrowly-defined cognitive tasks.

Generalizing these assertions, however, is challenging, given the task-specificity of many studies, and the complexity of the underlying physiological system. Therefore, we recommend that baselines should be established on a peer-activity basis. Another challenge is the high inter- and intra-individual differences in neurophysiological measurements. Brain activity might not only be different between participants but also change within one participant conducting exactly the same task more often due to plastic processes of neural activation as a consequence of learning.

A particular challenge to neurophysiological measurements is confirming their measured outputs provide true proxies for learning efficacy. High levels of what might be described as attention - for example alpha wave activity within a given threshold - do not necessarily correlate with attention towards the desired learning material. In game environments that use a wide range of stimuli, such as rapid images, auditory content, and significant physical engagement with the interface, many behaviours and actions contribute to measurements, and can easily overwhelm attempts to isolate or consider specific learning processes. Because of these influences it is sometimes very difficult or even impossible to unequivocally interpret the results of neurophysiological measurements that have been recorded during acting in a game environment. Therefore, it is tremendously important to have a well-elaborated study design using conditions that are comparable with each other or are organized according to a factorial schema. This implies to use control conditions that are closest to the stimulus or task condition as baseline. This modus operandi is very important for neurophysiological research and especially important for fMRI-studies (Brandt, 2006).

Presence also plays a key role in how users respond and act within a virtual environment (VE). An increased presence experience in a VE should foster the transfer of knowledge acquired in the virtual environment to corresponding real world behaviour (Slater et al., 1996). This assumption is very important for serious games which base learning around interactions within a VE. Therefore it seems advisable to use VEs which can increase the sense of being there (presence) for game based learning. However, presence experience is difficult to measure, due to the subjective character of this concept.

A recent study by Kober and Neuper (2012) showed that ERPs in EEG can be used as a valuable and objective method for measuring presence in VEs. The highlighted studies in this review demonstrate the huge potential neurophysiological measurements have for the research of serious games and virtual environments (e.g. measuring subjective experiences in VEs and serious game: Klasen et al. 2012; Kober and Neuper, 2012; using neurophysiological signals as an extra modality for game design: Lin and John, 2006; Scherer et al., 2011; etc.).

----- Figure 1 around here -----

4. Summary and Conclusions

The paper summarises some of the leading scientific research studies in the emerging field of neuroscience applied to gaming where EEG, fMRI and fNIRS are used to investigate the learner's brain activity during game play. The findings indicate that there is a need to focus study designs in a particular way (see also Figure 1), as addressed in the discussion, to ensure that these are effective, focused on direct task performance and thereby narrowing the variables.

The review indicates that there are key benefits in using these neuroscientific techniques for developing serious games, particularly to provide better user feedback and allow designers to get a better understanding of the neurophysiological outcomes of the learner during learning periods and tasks.

The review presented in this paper has scoped the extent of the literature around using EEG, fNIRS and fMRI within game environments for supporting feedback but also for allowing us to trace the impact of game activities within brain activity. Our ambition is to extend the scope of how neurofeedback is currently used in games, as real time data that can be used to support scaffolded learning and also to allow us to understand more about how game play supports effective learning.

Future work will therefore focus upon user studies where simple and complex learning activities are tested using neurophysiological correlates according to direct task performance with different neurophysiological methods. This approach enables to identify the best applications and uses of these methods for supporting human computer interaction in games environments. The state of the art clearly shows the potential for using these devices. However, we strongly argue that it is hard time to study a rigorous, generalizable method for capturing neuroscientific user data from a player and store it in a real-time executable user model, also extending existing models of feedback (e.g. Dunwell, de Freitas, and Jarvis, 2011).

Further future research will focus on testing how feedback can be used in real time to make the learner experience more coherent and immersive, as well as recording levels of presence and engagement. Our future work will therefore aim to provide a scientific basis for utilizing neurophysiological interaction with learners during learning activities and tasks in game environments and will also aim to develop a common methodological approach. Ecological validity, interest and motivators may come at costs of straightforwardness in interpretation of neurophysiological data. Yet, there are ways to reach a balance between both things.

Figures:




Figure 1: Visualization of the planning process of an experiment and summing up relevant points from the discussion

REFERENCES

- Allison, B., & Polich, J. (2008) 'Workload assessment of computer gaming using a single-stimulus event-related potential paradigm', *Biological psychology*, Vol. 77, No. 3, pp.277 – 283.
- Arnab, S., Petridis, P., Dunwell, I., de Freitas, S. (2010) 'Touching artefacts in an ancient world on a browser-based platform', *IADIS International Conference: Web Virtual Reality and Three-Dimensional Worlds 2010*, Freiburg, Germany, 27 - 29 July 2010.
- Basak, C., Boot, W.R., Voss, M.W., Kramer, A.F. (2008) 'Can Training in a Real-Time Strategy Video Game Attenuate Cognitive Decline in Older Adults?', *Psychology and Aging*, Vol. 23, No. 4, pp.765 - 777.
- Baumgartner, T., Speck, D., Wettstein, D., Masnari, O., Beeli, G., & Jäncke, L. (2008) 'Feeling present in arousing virtual reality worlds: prefrontal brain regions differentially orchestrate presence experience in adults and children', *Frontiers in Human Neuroscience*, Vol. 2, pp.1–2.
- Baumgartner, T., Valko, L., Esslen, M., & Jäncke, L. (2006) 'Neural correlate of spatial presence in an arousing and noninteractive virtual reality: an EEG and psychophysiology study', *Cyberpsychology & Behavior*, Vol. 9, No. 1, pp.30–45.
- Brandt, T. (2006) 'How to see what you are looking for in fMRI and PET – or the crucial baseline condition' *Journal of neurology*, Vo. 253, No. 5, pp.551-555.
- Bellotti F., Berta R. and De Gloria A. (2010) 'Designing Effective Serious Games: Opportunities and Challenges for Research', *Int. Journal of Emerging Technologies in Learning*, Special Issue: Creative Learning with Serious Games Vol. 5, pp.22-35.
- Bengtsson, S.L., Ullen, F., Ehrsson, H.H., Hashimoto, T., Kito, T., Naito, E., Forsberg, H., Sadato, N. (2009) 'Listening to rhythms activates motor and premotor cortices', *Cortex*, Vol. 45, No.1, pp.62-71.
- Boot, W.R., Kramer, A.F., Simons, D.J., Fabiani, M., Gratton, G. (2008) 'The effects of video game playing on attention, memory, and executive control', *Acta Psychologica*, Vol. 129, No. 3, pp.387-398.
- Chi, R.P & Snyder, A.W. (2012) 'Brain stimulation enables the solution of an inherently difficult problem', *Neuroscience Letters*, Vol. 515, No. 2, pp.121-124.
- Chisholm J.D., Hickey, C., Theeuwes, J., Kingstone, A. (2010) 'Reduced attentional capture in action video game players', *Attention, Perception, & Psychophysics*, Vol. 72, No. 3, pp.667-671.
- Clark, L. (2010) 'Decision-making during gambling: An integration of cognitive and psychobiological approaches', *Philosophical Transactions of the Royal Society B: Biological Sciences*, Vol. 365, No. 1538, pp.319-330.
- Cohen-Kadosh, R., Soskic, S., Iuculano, T., Kanai, R., Walsh, V. (2010) 'Modulating Neuronal Activity Produces Specific and Long-Lasting Changes in Numerical Competence', *Current Biology*, Vol. 20, No. 22, pp.2016-2020.

- de Freitas, S. & Maharg, P. (Eds), (2011) *Digital Games and Learning*, Continuum Press, London & New York.
- de Freitas, S. & Neumann, T. (2009) 'The use of 'exploratory learning' for supporting immersive learning in virtual environments', *Computers and Education*, Vol. 52, No. 2, pp.343-352.
- Derbali, L., & Frasson, C. (2010) 'Players' Motivation and EEG Waves Patterns in a Serious Game Environment', in V. Aleven, J. Kay, & J. Mostow (Eds.), *In Intelligent Tutoring Systems*, Vol. 6095, Springer-Verlag: Berlin Heidelberg, pp.297-299
- Detre J.A., & Wang, J. (2002) 'Technical aspects and utility of fMRI using BOLD and ASL', *Clinical Neurophysiology*, Vol. 113, No. 5, pp.621-634.
- Dietrich, A., & Kanso, R.. (2010) 'A review of EEG, ERP, and neuroimaging studies of creativity and insight', *Psychological Bulletin*, Vol. 136, No. 5, pp.822-848.
- Dourish, P., Bellotti, V. (1992) 'Awareness and Coordination in Shared Workspaces', *CSCW '92: Proceedings of the 1992 ACM conference on Computer-supported cooperative work*, Toronto, Canada.
- Dumas, G. Nadel, J., Soussignan, R., Martinerie, J., Garnero, L. (2010) 'Inter-brain synchronization during social interaction', *PLoS ONE*, Vol. 5, No. 1, Article number e12166.
- Dunwell, I., de Freitas, S., Jarvis, S. (2011) 'Four-dimensional consideration of feedback in serious games', In *Digital Games and Learning*, de Freitas, S. and Maharg, P.(Eds.), Continuum Publishing, London & New York , pp.42-62.
- Feng, J., Spence, I., Pratt, J. (2007) 'Playing an action video game reduces gender differences in spatial cognition'. *Psychological Science*, Vol. 18, No. 10, pp.850-855.
- Ferrari, M., & Quaresima, V. (2012) 'A brief review on the history of human functional near-infrared spectroscopy (fNIRS) development and fields of application', *Neuroimage*, Vol. 63, No. 2, pp.921-935.
- Fink, A., Grabner, R.H., Gebauer, D., Reishofer, G., Koschutnig, K., Ebner, F. (2010) 'Enhancing creativity by means of cognitive stimulation: Evidence from an fMRI study', *NeuroImage*, Vol. 52, No. 4, pp.1687-1695.
- Fink, A., Graif, B., Neubauer, A.C. (2009) 'Brain correlates underlying creative thinking: EEG alpha activity in professional vs. novice dancers', *Neuroimage*, Vol. 46, No. 3, pp.854-862.
- Finke, A., Lenhardt, A., Ritter, H.(2009) 'The MindGame: A P300-based BCI game', *Neural Networks*, Vol. 22, pp.1329-1333.
- Flöel, A., Rösler, N., Michka, O., Knecht, S., Breitenstein C. (2008) 'Non-invasive brain stimulation improves language learning', *Journal of Cognitive Neuroscience*, Vol. 20, No. 8, pp.1415-1422.

- Girouard, A., Solovey, E., Hirshfield, L., Chauncey, K., Sassaroli, A., Fantini, S., Jacob, R.J. (2009) 'Distinguishing Difficulty Levels with Non-invasive Brain Activity Measurements', *INTERACT '09 Proceedings of the 12th IFIP TC 13 International Conference on Human-Computer Interaction: Part I*, Uppsala, Sweden, pp.440-452.
- Goebel, R., Sorger, B., Kaiser, J., Birbaumer, N., & Weiskopf, N. (2004) 'BOLD brain pong: Self regulation of local brain activity during synchronously scanned, interacting subjects', *34th Annual Meeting of the Society for Neuroscience*.
- Green, C.S. & Bavelier, D. (2003) 'Action video game modifies visual selective attention', *Nature*, Vol. 423, No. 6939, pp.534-537.
- Green, C.S., Li, R., Bavelier, D. (2010) 'Perceptual Learning During Action Video Game Playing', *Topics in Cognitive Science*, Vol. 2, No. 2, pp.202-216.
- Haier, R.J. & Jung, R.E. (2008) 'Brain Imaging Studies of Intelligence and Creativity: What is the Picture for Education?', *Roeper Review*, Vol. 30, No. 3, pp.171-180.
- Halimi, K., Seridi, H., & Faron-Zucker, C. (2011) 'SoLearn: a Social Learning Network', in *Proc. Of: Third International Conference on Computational Aspects of Social Networks (CASoN'11)*, 19-21, October 2011, Salamanca, Spain.
- Hattahara, S., Fujii, N., Nagae, S., Kazai, K., & Katayose, H. (2008) 'Brain activity during playing video game correlates with player level'. In M. Inakage & A. D. Cheok (Eds.), *Proceedings of the International Conference on Advances in Computer Entertainment Technology. ACE 2008 : December 3rd-5th, 2008, Yokohama, Japan*. Association for Computing Machinery: New York, N.Y.
- Huettel, S. A., Song, A. W., & McCarthy, G. (2009) *Functional Magnetic Resonance Imaging*, 2nd ed., Sinauer Associates, Massachusetts.
- Hummer, T. A., Wang, Y., Kronenberger, W. G., Mosier, K. M., Kalnin, A. J., Dunn, D. W., & Mathews, V. P. (2010) 'Short-Term Violent Video Game Play by Adolescents Alters Prefrontal Activity During Cognitive Inhibition', *Media Psychology*, Vol. 13, No. 2, pp.136-154.
- Huppert, T. J., Hoge, R. D., Diamond, S. G., Franceschini, M. a, & Boas, D. a. (2006) 'A temporal comparison of BOLD, ASL, and NIRS hemodynamic responses to motor stimuli in adult humans', *NeuroImage*, Vol. 29, No. 2, pp.368-82.
- Izzetoglu, K., Bunce, S., Onaral, B., Pourrezaei, K., & Chance, B. (2004) 'Functional Optical Brain Imaging Using Near-Infrared During Cognitive Tasks', *International Journal of Human-Computer Interaction*, Vol. 17, No. 2, pp.211-227.
- Jäncke, L., Cheetham, M., & Baumgartner, T. (2009) 'Virtual reality and the role of the prefrontal cortex in adults and children', *Frontiers in neuroscience*, Vol. 3, No. 1, pp.52-59.
- Kalyuga, S., Chandler, P., & Sweller, J. (2004) 'When redundant on-screen text in multimedia technical instruction can interfere with learning', *Human Factors: The Journal of the Human Factors and Ergonomics Society*, Vo. 46, No. 3, pp.567-581.

- Klasen, M., Weber, R., Kircher T.T.J., Mathiak, K.A. and Mathiak, K. (2012) ,Neural contributions to flow experience during video game playing', *Social Cognitive and Affective Neuroscience*, Vol. 7, No. 4, pp.485-495.
- Knight, J., Carly, S., Tregunna, B., Jarvis, S., Smithies, R., de Freitas, S., Mackway-Jones, K. & Dunwell, I. (2010) 'Serious gaming technology in major incident triage training: A pragmatic controlled trial', *Resuscitation Journal*, Vol. 81, No. 9, pp.1174-1179.
- Kober, S.E. & Neuper, C. (2012) ,Using auditory event-related EEG potentials to assess presence in virtual reality', *Int. J. Human-Computer Studies*, Vol 70, pp.577-587.
- Kober, S. E., Kurzmann, J., & Neuper, C. (2012) 'Cortical correlate of spatial presence in 2D and 3D interactive virtual reality: An EEG study', *International Journal of Psychophysiology*, Vol. 83, No. 3, pp.365-374.
- Kosmadoudi, Z., Sung, R.C.W., Liu, Y., Lim, T., Ritchie, J. (2010) 'Evaluating user interfaces for engineering tasks with biometric logging', *TMCE Proceedings*, Vol. 2, pp.267-277.
- Kramer, D. (2007) 'Predictions of Performance by EEG and Skin Conductance', *Indiana Undergraduate Journal of Cognitive Science*, Vol. 2, pp.3–13.
- Kropotov, J. (2009) *Quantitative EEG, event-related potentials and neurotherapy*, 1st ed., Elsevier Academic Press, San Diego.
- Liarokapis, F., Macan, L., Malone, G., Rebolledo-Mendez, G. & de Freitas, S. (2009) 'A Pervasive Augmented Reality Serious Game', *Proc. of the 1st IEEE International Conference in Games and Virtual Worlds for Serious Applications, IEEE Computer Society*, Coventry, UK, 23-24 March, pp.148-155.
- Lin, T.A. & John, L.R. (2006) 'Quantifying Mental Relaxation with EEG for use in Computer Games'. *International Conference on Internet Computing*, pp.409–415.
- Liu, Y., Kosmadoudi, Z., Sung, R.C.W., Lim, T., Ritchie, J. (2010) 'Capture User Emotions during Computer- Aided Design', *IDMME Proceedings*, Vol. 3, pp.65 – 66.
- Lloyd-Fox, S., Blasi, a, & Elwell, C. E. (2010) 'Illuminating the developing brain: the past, present and future of functional near infrared spectroscopy', *Neuroscience and biobehavioral reviews*, Vol. 34, No. 3, pp.269–84.
- Maguire, E. A., Burgess, N., & O'Keefe, J. (1999) 'Human spatial navigation: cognitive maps, sexual dimorphism, and neural substrates', *Current Opinion in Neurobiology*, Vol. 9, No. 2, pp.171–177.
- Maguire, E. A., Burgess, N., Donnett, J. G., Frackowiak, R. S. J., Frith, C. D., & O'Keefe, J. (1998) 'Knowing Where and Getting There: A Human Navigation Network', *Science*, Vol. 280, pp.921–924.
- Martena, S., Dicke, P.W., & Thier, P. (2008) 'Dissociable Roles of the Superior Temporal Sulcus and the

- Intraparietal Sulcus in Joint Attention: A Functional Magnetic Resonance Imaging Study', *Journal of Cognitive Neuroscience*, Vol. 20, No. 1, pp.108-119.
- Mathiak, K., & Weber, R. (2006) 'Toward brain correlates of natural behavior: fMRI during violent video games', *Human brain mapping*, Vol. 27, No.12, pp.948–956.
- Matsuda, G., & Hiraki, K. (2006) 'Sustained decrease in oxygenated hemoglobin during video games in the dorsal prefrontal cortex: a NIRS study of children', *NeuroImage*, Vol. 29, No. 3, pp.706– 711.
- Matsuyama, H., Asama, H., & Otake, M. (2009) 'Design of differential Near-Infrared Spectroscopy based Brain Machine Interface', *RO-MAN 2009 - The 18th IEEE International Symposium on Robot and Human Interactive Communication*, pp.775–780.
- Muehleman, T., Haensse, D., & Wolf, M. (2008) 'Wireless miniaturized in-vivo near infrared imaging', *Optics express*, Vol. 16, No. 14, pp.10323–10330
- Nacke, L. E., Grimshaw, M. N., & Lindley, C. A. (2010) 'More than a feeling: Measurement of sonic user experience and psychophysiology in a first-person shooter game', *Interacting with Computers*, Vol. 22, No. 5, pp.336–343.
- Naeem, M., Prasad, G., Watson, D.R., Kelso, J.A. (2012) 'Electrophysiological signatures of intentional social coordination in the 10-12 Hz range', *Neuroimage*, Vol. 59, pp.1795-1803.
- Nagamitsu, S., Nagano, M., Yamashita, Y., Takashima, S., & Matsuishi, T. (2006) 'Prefrontal cerebral blood volume patterns while playing video games--a near-infrared spectroscopy study', *Brain & development*, Vol. 28, No. 5, pp.315–321.
- Nambu, I., Osu, R., Sato, M., Ando, S., Kawato, M., & Naito, E. (2009) 'Single-trial reconstruction of finger-pinch forces from human motor-cortical activation measured by near-infrared spectroscopy (NIRS)', *NeuroImage*, Vol. 47, No. 2, pp.628–37.
- Niedermeyer, E., & Lopes da Silva, H. (Eds.). (2005) *Electroencephalography: Basic Principles, Clinical Applications, and Related Fields* (5th ed.), Lippincott Williams & Wilkins: Baltimore.
- Nijholt, A., Plass-Oude Bos, D., Reuderink, B. (2009) 'Turning shortcomings into challenges: brain–computer interfaces for games', *Entertainment Computing*, Vol. 1, No. 2, pp.85-94.
- Ninaus, M., Witte, M., Kober, S. E., Friedrich, E. V. C., Kurzmann, J., Hartsuiker, E., Neuper, C., Wood, G. (2013) 'Neurofeedback and Serious Games', in Connolly, T. M et al. (Eds.), *Psychology, Pedagogy and Assessment in Serious Games*. Hershey, PA: IGI Global, in Press.
- Oberman, L.M., McCleery, J.P., Ramachandran, V.S., Pineda, J. (2007) 'EEG evidence for mirror neuron activity during the observation of human and robot actions: Toward an analysis of the human qualities of interactive robots', *Neurocomputing*, Vol. 70, pp.2194-2203.
- Pellouchoud, E., Smith, M. E., McEvoy, L., & Gevins, A. (1999) 'Mental effort-related EEG modulation during video-game play: comparison between juvenile subjects with epilepsy and normal control subjects', *Epilepsia*, Vol. 40, Suppl. 4, pp.38–43.

- Pfurtscheller, G. (1989) 'Spatiotemporal analysis of alpha frequency components with the ERD technique', *Brain topography*, Vol. 2, No. 1-2, pp.3–8.
- Pfurtscheller, G., & Lopes, d. (1999) 'Event-related EEG/MEG synchronization and desynchronization: basic principles', *Clinical Neurophysiology*, Vol. 110, No. 11, pp.1842–1857.
- Plotnikov A., Stakheika N., De Gloria A., Schatten C., Bellotti F., Berta R., Fiorini C., Ansovini F. 'Exploiting real-time EEG analysis for assessing flow in games', *Workshop:Game based learning for 21st century transferable skills*, at iCalt 2012, Rome, Italy, June 2012
- Premsky, M. (2003) 'Digital game-based learning'. *ACM Computers in Entertainment*, Vol.1, No.1, doi: 10.1145/950566.950596.
- Pugnetti, L., Mendozzi, L., Barberi, E., Rose, F. D., & Attree, E. A. (1996) Nervous system correlates of virtual reality experience. *Proc. 1st Euro. Conf. Disability, Virtual Reality & Assoc. Tech., Maidenhead, UK.*
- Rebolledo-Mendez, G., Dunwell, I., Martvnez-Miron, E.A., Vargas-Cerdan, M.D., de Freitas, S., Liarokapis, F. & Garcia-Gaona, A.R., (2009) 'Assessing the Usability of a Brain-Computer Interface (BCI) that Detects Attention Levels in an Assessment Exercise', *Proceedings of the 13th International Conference on Human-Computer Interaction*, Springer Lecture Notes In Computer Science, San Diego, California, USA, 19-24 July.
- Rebolledo-Mendez, G., Sosa-Jimenez, C., Gabriel Acosta-Mesa, H. & de Freitas, S. (under review) 'Evaluating supervised learning algorithms to classify cognitive states using a commercial BCI', In *Advances in Human Computer Interactions*.
- Reis, J., Schambra, H.M., Cohen, L.G., Buch, E.R., Fritsch, B. Zarahn, E., Celnik, P.A., Krakauer, J.W. (2009) 'Noninvasive cortical stimulation enhances motor skill acquisition over multiple days through an effect on consolidation', *Proceedings of the National Academy of Sciences USA*, Vol. 106, No. 5, pp.1590-1595.
- Rizzolatti, G., Craighero, L. (2004) 'The Mirror-neuron system', *Annual Review of Neuroscience*, Vol. 27, pp.169-192.
- Roschelle, J. and Teasley, S. (1995) 'The construction of shared knowledge in collaborative problem solving', in O'Malley, C.E., (Ed.), *Computer Supported Collaborative Learning*, pp.69-97. Springer-Verlag, Heidelberg.
- Saito, K., Mukawa, N., & Saito, M. (2007) 'Brain Activity Comparison of Different-Genre Video Game Players', In D. U. IEEE Computer Society Washington (Ed.), *Proceedings of the Second International Conference on Innovative Computing, Information and Control*, p. 402.
- Salminen, M., & Ravaja, N. (2007) 'Oscillatory brain responses evoked by video game events: the case of super monkey ball 2', *Cyberpsychology & behavior : the impact of the Internet, multimedia and virtual reality on behavior and society*, Vol. 10, No. 3, pp.330–338.

- Salminen, M., & Ravaja, N. (2008) 'Increased oscillatory theta activation evoked by violent digital game events', *Neuroscience letters*, Vol. 435, No. 1, pp.69–72.
- Scherer, R., Faller, J., Balderas, D., Friedrich, E.V.C., Pröll, M., Allison, B., Müller-Putz, G. (2013) 'Brain-computer interfacing: more than the sum of its parts', *Soft Computing*, Vol. 17, No. 2, pp.317-331.
- Shams, L. & Seitz, A.R. (2008) 'Benefits of multisensory learning', *Trends in Cognitive Sciences*, Vol. 12, No. 11, pp.411-417.
- Sharot, T., Martorella, E. A., Delgado, M. R., Phelps, E. A. (2007) 'How personal experience modulates the neural circuitry of memories of September 11' *Proceedings of the National Academy of Sciences USA*, Vol. 104, No. 1, pp.389-394.
- Sharot, T., Velasquez, C. M., & Dolan, R. J. (2010) 'Do decisions shape preference? Evidence from blind choice', *Psychological Science*, Vol. 21, No. 9, pp.1231-1235.
- Sitaram, R., Caria, A., & Birbaumer, N. (2009) 'Hemodynamic brain-computer interfaces for communication and rehabilitation', *Neural networks*, Vol. 22, No. 9, pp.1320–1328.
- Slater, M., Linakis, V., Usuh, M., Kooper, R. (1996) In: Mark, Green(Ed.), *Immersion, Presence and Performance in Virtual Environments: An Experiment with Tri-Dimensional Chess. ACM Virtual Reality Software and Technology (VRST)*, pp.163–172.
- Slater, M. (2003) 'A note on presence terminology' *Presence connect*, Vol. 3, No. 3.
- Sternberg, S. (1969) 'The discovery of processing stages: Extensions of Donders' method', *Acta Psychologica*, Vol. 30, pp. 276-315.
- Strehl, U., Leins, U., Goth, G., Klinger, C., Hinterberger, T., & Birbaumer, N. (2006) 'Self-regulation of Slow Cortical Potentials: A New Treatment for Children with Attention-Deficit/Hyperactivity Disorder' *Pediatrics*, Vol. 118, No. 5, pp.e1530-e1540
- Suilleabhain, G. O. (2008) 'Player transfer: How learning transfer and serious games answer serious (and transferable) questions about one another', In T. Conolly & M. Stansfield (Eds.), *Proceedings of the 2nd European Conference on Games Based Learning*, Academic Publishing Limited, Barcelona, Spain, pp.349- 356.
- Tachibana, A., Noah, J. A., Bronner, S., Ono, Y., & Onozuka, M. (2011) 'Parietal and temporal activity during a multimodal dance video game: an fNIRS study', *Neuroscience letters*, Vol. 503, No. 2, pp.125–30.
- Ventur, B., Blankertz, B., Gugler, M., Curio, G., (2010) 'Novel Applications of BCI Technology: Psychophysiological Optimization of Working Conditions in Industry'. *Proc. Int. Conf. Systems, Man, and Cybernetics 2010*.
- Telkemeyer, S., Rossi, S., Nierhaus, T., Steinbrink, J., Obrig, H., & Wartenburger, I. (2011) 'Acoustic processing of temporally modulated sounds in infants: evidence from a combined near-infrared

spectroscopy and EEG study', *Frontiers in psychology*, Vol.2, pp.1-14.

Villringer, A., & Chance, B. (1997) 'Non-invasive optical spectroscopy and imaging of human brain function', *Trends in neurosciences*, Vol. 20, No. 10, pp.435-42.

Wang, Y., Mathews, V. P., Kalnin, A. J., Mosier, K. M., Dunn, D. W., Saykin, A. J., & Kronenberger, W. G. (2009) 'Short Term Exposure to a Violent Video Game Induces Changes in Frontolimbic Circuitry in Adolescents', *Brain Imaging and Behavior*, Vol. 3, No. 1, pp.38-50.

Weiskopf, N. (2012) 'Real-time fMRI and its application to neurofeedback', *NeuroImage*, Vol. 62, No. 2, pp.682-692.

Williams, J.H.G., Waiter, G.D., Perra, O., Perrett, D.I., Whiten, A. (2005) 'An fMRI study of joint attention experience' *NeuroImage*, Vol. 25, No. 1, pp.133-140.

Yamada, F. (1998) 'Frontal midline theta rhythm and eyeblinking activity during a VDT task and a video game: useful tools for psychophysiology in ergonomics' *Ergonomics*, Vol. 41, No. 5, pp.678-688.

Yoo, J.J., Hinds, O., Ofen, N., Thompson, T.W., Whitfield-Gabrieli, S., Triantafyllou, C., Gabrieli, J.D.E. (2012) 'When the brain is prepared to learn: Enhancing human learning using real-time fMRI' *Neuroimage*, Vol. 59, No. 1, pp.846-852.

Zander, T.O. and Kothe, C. (2011) 'Towards passive BCI: applying BCI technology for human-machine systems in general', *Journal of Neural Engineering*, Vol. 8, pp.1-5.

Zyda, M. (2005) 'From Visual Simulation to Virtual Reality to Games', *IEEE Computer*, Vol. 38, No.9, pp.25-31.